RECYCLING








Applications

- Press
- Compactor
- Shredder

- Shaft Grinder
- Mill
- Shears Press

- Coil Press Binder
- Extractor Centrifuge





- Manifold, HPU (Hydraulic Power Unit) and Integrated System full engineering
- Fluid dynamics simulation
- Structural calculation
- Deep analysis and check of every single system parameter with specific and official report release
- Final operational test of the whole system
- World Wide commissioning with high level expertise technicians
- Rigid and flexible piping and on-site full assistance
- 40 years-experience in the hydraulic field and a very passionate team of engineers and technicians who work every day close to our customers







Key Components



- High-Low Pressure switches
- High Flow Cartridge Valves
- High Performance Air/Oil Heat Exchangers
- Manifold with up to 1m long drilled holes
- High Capacity Accumulators

Expertise

Power: up to 640 kW [860 hp]

Flow rate: up to 6.000 l/min [1590 gpm]

Pressure: up to 420 bar [6000 psi]

Temperature: -40 °C +60 °C [-40 °F +140 °F]

Certifications: according to: SIL, PED requirements

Process Control: WPS, PQR, NDT, mechanical stress and wearing tests

Engineering international UNI EN ISO 13849, ASME, EU Directives rules and specifications

standards: IEC61508, IEC61511

Painting: based on customer specifications

Surface treatments: galvanization, phosphating, electrolytic protections, nitrocarburizing, stainless steel

surface finishing

Materials: steel, cast iron, ergal



